



Conductivity



Sound Velocity



Pressure



Turbidity

And More.....

Xchange™ is the industry's leading family of field-swappable sensor heads. Each sensor head contains its own embedded calibration and can be moved from instrument to instrument without impacting accuracy. Changing sensors is easy: simply unscrew one sensor head and replace it with another.

### Key Benefits:

- **Zero Down Time** - With X2 series sensors, recalibrated sensors are sent to the instrument instead of sending the instrument to the recalibration centre.
- **Reduce Logistical Costs** - With X2 series small sensor heads are shipped instead of heavy instruments.
- **Increased Flexibility** - Field-swappable sensor heads enable any organization - big or small - to become a virtual recalibration centre by stocking spare calibrated sensor heads.
- **One Instrument, Multiple Applications** - the ability to change sensor type on any instrument to suit specific application requirements. This means instrument duplicates (identical instruments dedicated to different pressure ranges, separate instrument for Turbidity, pH, Chlorophyll, etc) become a thing of the past.
- **Improved absolute pressure accuracy** - You may choose the best full scale pressure range to suit your deployment depth.

Xchange™ sensor heads are used exclusively with X2-Series / Orange Line instrumentation. Total flexibility of instrument model, sensor type, and sensor range ensures that the right instrument is always available. Please refer to the X2-Series brochure for a list of instruments, applications, and specifications.

**Sound Velocity / CTD / Multiparameter / Biofouling Control / Deployment Systems**

	Max Depth (m)	Range	Precision (+/-)	Accuracy (+/-)	Resolution	Response Time	Notes
<b>Conductivity &amp; Temperature</b>	6000 <sup>1</sup>	C: 0-90 mS/cm <sup>2</sup> T: -5 - 45 °C	C: 0.003 mS/cm T: 0.003 °C TMP: 0.003 °C	C: 0.01 mS/cm <sup>6</sup> or 0.003mS/cm <sup>6</sup> T: 0.005 °C or 0.002 °C	C: 0.001 mS/cm T: 0.001 °C	C: 25 ms T: 100 ms	Combined Conductivity & Temperature
<b>Sound Velocity</b>	6000 <sup>1</sup>	1375-1625 m/s	0.006 m/s	0.025 m/s	0.001 m/s	20 ms	
<b>Sound Velocity &amp; Temperature</b>	6000 <sup>1</sup>	SV: 1375-1625 m/s	0.006 m/s T: 0.003 °C	SV: 0.025 m/s T: 0.005 °C	SV: 0.001 m/s T: 0.001 °C	SV: 20 ms T: 550 ms	Combined Sound Velocity & Temperature
<b>Pressure Sensor</b>	100 - 6,000	0-100 dBar to 0 to 6,000 dBar	0.03% FS	0.05% FS	0.02% FS	10 ms	Piezo-Resistive
<b>Turbidity</b> <small>Powered by Turner</small>	200	0-1500 NTU <sup>4</sup>	0.5% reading or 0.1 NTU <sup>5</sup>	2% reading or 0.2 NTU <sup>5</sup>	0.01 NTU	<0.7 s	
	200	0-3000 NTU <sup>4</sup>	0.04% NTU <sup>5</sup> or 0.1 NTU <sup>5</sup>	Linearity 0.99 R <sup>2</sup>	0.01 NTU	<0.7 s	Wiper-equipped
<b>Chlorophyll</b> <small>Powered by Turner</small>	600	0-500 µg/L	± 0.05% FS	Linearity 0.99 R <sup>2</sup>	200 ms		A & B Red Excitation
	600	0-500 µg/L					A & B Blue Excitation High CDOM
<b>pH</b> <small>Powered by Idronaut</small>	1500	0 to 14	± 0.05% FS	± 0.1			KCl Reference: Ideal for fast response profiling applications
	6000						KCl Reference: Ideal for fast response profiling applications
	1500						NaCl Reference: Ideal for long term in-situ deployments
	6000						NaCl Reference: Ideal for long term in-situ deployments
<b>Phycoerythrin (BGA)</b>		0 to 750 ppb					
<b>CDOM/FDOM</b>		0-1250 ppb					
<b>Flourescein</b>		0-500 ppb					
<b>Rhodamine</b>	600	0-1000 ppb	± 0.05% FS	Linearity 0.99 R <sup>2</sup>	200 ms		X2 Series optical sensors are powered by Turner
<b>Crude Oils</b>		>10000 ppb					
<b>Refined Fuels</b>		>100 ppm					
<b>Tryptophan</b>		0-5000 ppb					
<b>Optical Brighteners</b>		0-5000 ppb					

Additional Sensors in both X2Change and Cabled Configurations are available upon request. All specifications subject to change without notice.

<sup>1</sup> Survivable to 11000 m. Inquire for specifications.

<sup>2</sup> Will over-range to 100 mS/cm. Inquire for specifications.

<sup>3</sup> Will over-range to 60 °C. Inquire for specifications.

<sup>4</sup> Digital auto-ranging

<sup>5</sup> Whichever is greater

<sup>6</sup> Stability is +/-0.003 mS/cm/month when combined with UV UVUV-Xchange™

rev201103